



## ARA SAFETY PRO<sup>™</sup>

The Ara Safety Pro<sup>™</sup> initial attack tool buys time, makes the fireground safer and reduces property loss. When deployed, a non-toxic aerosol rapidly knocks down flame and temperature for critical minutes while crews set up for attack and overhaul.

### SPECIFICATIONS

- Effective for use against class A, B, and C fires
- Weight of active ingredient: 2.6 kg
- Total weight: 4.08 kg
- Diameter: 220 mm
- Height: 80 mm
- Protection capacity: 60m<sup>3</sup> (2100 ft<sup>3</sup>)
- Activation Delay: 5 - 8 seconds
- Time of aerosol discharge: 20 - 28 seconds
- 5 year limited warranty

## ARA SAFETY PRO<sup>™</sup> CASE

### STANDARD FEATURES

- Waterproof
- Impact resistant
- Soft grip foldable handle
- Automatic pressure release valve
- Stackable
- Powerclaw latching system
- Crushproof
- Dustproof

### CASE SPECIFICATIONS

- Exterior dimension: L 15.8" x W 12.1" x H 6.8"
- Weight (empty): 4.4 lbs (2.0 kg)
- Material: lightweight NK-7 resin
- Max buoyancy: 35 lbs (15.88 kg)



## ARA SAFETY PRO<sup>™</sup> MOUNTING BRACKET

### STANDARD FEATURES

- NFPA compliant
- Easy to install
- Fully adjustable
- Capable of 5400 psi
- Strap can be elongated up to 535% its original length before breaking
- Made from high strength Pellethane elastomer
- Mounts to Uni-Strut channel



**ARA SAFETY**<sup>™</sup>  
[www.arasafety.com](http://www.arasafety.com)

Locate your nearest dealer  
 1-888-955-8883 sales@arasafety.com

CALL YOUR LOCAL ARA AUTHORIZED DEALER